



CONNECT PLUS MULTI-SITE DIGITAL TRUNKING SYSTEM

MOTOTRBO™ XRT 9000 GATEWAY

Keep your workforce connected. When you fleet is dispatched across the city and your workers are miles apart, you need a way to stay connected. Scalable to meet your communication needs, Connect Plus multi-site trunking is a two-way radio system that enables your work teams to not only share voice communication, they can also use integrated data applications to make their job more efficient and safer, including text messaging, location tracking and dispatch capability. All the while, you gain the benefits of TDMA digital technology like increased capacity and clear audio.

EXCEPTIONAL ACCESS

Centralized access to your workforce

Keep connected with a large workforce operating in the field by using the MOTOTRBO XRT 9000 gateway to link your MOTOTRBO Connect Plus system with an IP-based wire-line console for centralized dispatch capability.

Versatile performance management

Monitor, report and analyze system performance by using the MOTOTRBO XRT 9000 gateway to link your MOTOTRBO Connect Plus system with performance management applications.

SUPERIOR CALL TRAFFIC MANAGEMENT

Scalable to meet your needs

Get calls through even when volume is high. From a single-site system to a 35-site system, each MOTOTRBO XRT 9000 gateway can handle up to 100 Registered Talkpaths and 30 simultaneous calls at a time. Up to five (5) XRT 9000 Gateways can be added to a Connect Plus system to provide additional capacity for the most demanding system and dispatching needs.

PRODUCT SPEC SHEET
XRT 9000

SPECIFICATIONS			
	MODEL TT2393A	MODEL TT2392A	MODEL TT2394A
	MOTOTRBO XRT 9000 Gateway 30 simultaneous + 0 Registered Talkpaths	MOTOTRBO XRT 9000 Gateway 30 simultaneous + 100 Registered Talkpaths	MOTOTRBO XRT 9000 Gateway Adds block of 10 Registered Talkpaths (Licenses only)
Performance	Celeron M, 1 GHz Microprocessor		
Ethernet Connections	4-Auto sensing 10/100/1000 Mbps Ports		
Serial Connections	8- RS232 Ports		
Operating System	Wind River Linux		
AC Input Power Requirements	100/240 VAC, 47 to 63 Hz, 50 Watts fully loaded		
Standard Warranty	Two years		

Specifications subject to change without notice. All specifications shown are typical.

Gateway meets applicable regulatory requirements.

PHYSICAL CHARACTERISTICS	
Dimensions	440 x 253 x 90 mm (17.32 x 9.96 x 3.54 inches) (without mounting tabs)
Mounting	Standard 19" rack mounting
Weight	7 kg (15.4 lbs)

ENVIRONMENTAL	
Operating Temperature	-30 to +60°C (-22 to +142°F)
Humidity	5 to 95% RH
Storage Temperature	-40 to +85°C (-40 to +185°F)

STANDARDS	
FCC	Part 15 Subpart B, CISPR 22 Class A
UL/cUL	UL60950-1, CSA C 22.2 No. 60950-1-03
EU	LVD EN60950-1

For more information on how to make your business more efficient and better connected, visit motorolasolutions.com/mototrbo or find your closest Motorola representative or authorised Partner at motorola.com/Business/XU-EN/Contact_Us

MOTOTRBO
DIGITAL
REMASTERED.

Distributed by:

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2012 Motorola Solutions, Inc. All rights reserved.

Motorola Solutions Ltd. Jays Close, Viabes Industrial Estate, Basingstoke, Hampshire, RG22 4PD, UK

EMEA version 1 (07/2012)

